

Wärmeleistung

Höhe H [mm]	Breite B [mm]	Naben- abstand N [mm]	Tiefe [mm]	Koeffi- zient	Heizkör- perexpo- nent n	Wärmeleistung bei					Elektro- Heizeinsatz W	An- strich- fläche m ²	Wasser- inhalt l	Ge- wicht kg
						76/65/ 20 °C W	76/65/ 20 °C W	76/65/ 20 °C W	76/65/ 20 °C W	76/65/ 20 °C W				
740	450	50	54	3,2448	1,2032	359	293	259	193	162	300	0,5601	2,87	6,40
	500	50	54	3,6329	1,1995	397	324	287	214	179	300	0,6104	3,07	6,90
	600	50	54	4,4407	1,1923	471	385	341	254	214	300	0,7109	3,48	7,86
1220	450	50	54	5,2576	1,2057	588	479	424	315	264	500	0,8681	4,51	10,32
	500	50	54	5,7020	1,2062	639	521	461	343	287	500	0,9435	4,81	11,12
	600	50	54	6,5859	1,2072	741	604	534	397	333	500	1,0943	5,42	12,72
1500	450	50	54	5,5056	1,2993	702	563	494	359	297	600	1,1021	5,68	12,11
	500	50	54	6,0000	1,2379	761	617	544	401	335	600	1,1994	6,08	13,04
	600	50	54	7,0044	1,2352	879	713	629	464	388	750	1,3942	6,86	14,88
	750	50	54	8,5503	1,2311	1056	857	757	559	467	750	1,6864	8,05	17,65
1820	450	50	54	6,7916	1,2398	868	703	620	457	382	750	1,3229	6,84	14,83
	500	50	54	7,2591	1,2432	939	760	671	494	412	750	1,4391	7,31	15,97
	600	50	54	8,1239	1,2501	1081	874	771	567	472	1000	1,6716	8,25	18,24
	750	50	54	9,3397	1,2605	1294	1045	920	675	561	1000	2,0203	9,66	21,66

Tab. 28 Wärmeleistung – Logatrend Therm Direct Q